



• • • •

• • • •

• • • •

• • • •

```

LL          IIIIII          SSSSSSSS
LL          IIIIII          SSSSSSSS
LL          II             SS
LL          II             SS
LL          II             SS
LL          II             SS
LL          II             SSSSSS
LL          II             SSSSSS
LL          II             SS
LL          II             SS
LL          II             SS
LL          II             SS
LLLLLLLLLLLL IIIIII          SSSSSSSS
LLLLLLLLLLLL IIIIII          SSSSSSSS

```

Mac  
---  
\$2  
-\$2  
TOT  
183  
The

(2)	56	HISTORY	; Detailed Current Edit History
(3)	85	DECLARATIONS	
(4)	129	FOR\$ENCODE_MF	- ENCODE formatted



```
0000 1 .TITLE FOR$ENCODE_MF - entry point for FORTRAN ENCODE FORMATTED
0000 2 .IDENT /1-011/ File: FORENCOMF.MAR Edit: JAW1011
0000 3
0000 4 *****
0000 5
0000 6 * COPYRIGHT (c) 1978, 1980, 1982, 1984 BY
0000 7 * DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS.
0000 8 * ALL RIGHTS RESERVED.
0000 9
0000 10 * THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED
0000 11 * ONLY IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE AND WITH THE
0000 12 * INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR ANY OTHER
0000 13 * COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY
0000 14 * OTHER PERSON. NO TITLE TO AND OWNERSHIP OF THE SOFTWARE IS HEREBY
0000 15 * TRANSFERRED.
0000 16
0000 17 * THE INFORMATION IN THIS SOFTWARE IS SUBJECT TO CHANGE WITHOUT NOTICE
0000 18 * AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT
0000 19 * CORPORATION.
0000 20
0000 21 * DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE OR RELIABILITY OF ITS
0000 22 * SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL.
0000 23
0000 24 *****
0000 25
0000 26
0000 27
0000 28 ++
0000 29 FACILITY: FORTRAN Support Library - user callable
0000 30
0000 31 ABSTRACT:
0000 32
0000 33 This module contains the entry point for the FORTRAN
0000 34 ENCODE FORMATTED I/O statement. It is simply
0000 35 a call to FOR$$IO_BEG with bits in R0 which describe the
0000 36 parameter list. FOR$$IO_BEG interprets the parameters.
0000 37
0000 38 MAINTENANCE NOTE:
0000 39 The transfer vector (RTLVECTOR+ALLGBL) must have the following:
0000 40
0000 41 .TRANSFER FOR$ENCODE_MF
0000 42 .MASK FOR$$IO_BEG
0000 43 BRW FOR$ENCODE_MF+2
0000 44
0000 45 This puts the correct mask in entry vector, that is FOR$$IO_BEG entry mask.
0000 46 Furthermore this module must only use R0 and R1
0000 47 since any other register might not be in the entry mask for FOR$$IO_BEG.
0000 48
0000 49 ENVIRONMENT: User access mode; mixture of AST level or not
0000 50
0000 51 AUTHOR: Richard B. Grove, CREATION DATE: 28-May-78
0000 52
0000 53 MODIFIED BY:
0000 54 T. Hastings, 29-July-78
```

```
0000 56      .SBTTL HISTORY      ; Detailed Current Edit History
0000 57
0000 58
0000 59 : Edit History for Version 1
0000 60
0000 61 : 0-10 - Add comment about vectors. TNH 23-June-78
0000 62 : 0-12 - Pass arg in R0, not R0R, add comments. TNH 29-July-78
0000 63 : 1-001 - Update version number and copyright notice. JBS 16-NOV-78
0000 64 : 1-002 - Change statement type symbols to be LUB$K... JBS 07-DEC-78
0000 65 : 1-003 - Change statement type symbols to be ISB$K... JBS 11-DEC-78
0000 66 : 1-004 - Add " " to the PSECT directive. JBS 22-DEC-78
0000 67 : 1-005 - Add FOR$READ_KF, FOR$READ_KO, FOR$REWRITE_SF, FOR$REWRITE_SO,
0000 68 : FOR$READ_IF, FOR$READ_IO, FOR$WRITE_IF, FOR$WRITE_IO,
0000 69 : FOR$READ_KU, FOR$REWRITE_SU,
0000 70 : SBL 2-May-1979
0000 71 : 1-006 - Remove all entry points that need object time formatting,
0000 72 : putting them in FOR$ENTRY_OBJ so that we can arrange to
0000 73 : load the format compiler only when it is needed.
0000 74 : JBS 26-JUN-1979
0000 75 : 1-007 - Remove entry point FOR$ENCODE_MF; we will code a new module
0000 76 : for it and FOR$$IO_BEG, to see how much I/O initiation time
0000 77 : improves. JBS 02-JUL-1979
0000 78 : 1-008 - Do likewise for FOR$READ_DU and FOR$WRITE_DU. JBS 03-JUL-1979
0000 79 : 1-009 - Remove all entry points except FOR$ENCODE_MF; each of the
0000 80 : others gets its own module so we can selectively load
0000 81 : the necessary UDF and REC modules. JBS 09-JUL-1979
0000 82 : 1-010 - New parameter format for FOR$$IO_BEG. SBL 5-Dec-1979
0000 83 : 1-011 - Change BRW FOR$$IO_BEG+2 to JMP G^FOR$$IO_BEG+2. JAW 21-Feb-1981
```



```
0000 85      .SBTTL  DECLARATIONS
0000 86
0000 87
0000 88  : INCLUDE FILES:
0000 89  :
0000 90
0000 91      $FORPAR      ; Define inter-module FORTRAN symbols
0000 92      $ISBDEF      ; Define statement type symbols
0000 93
0000 94  :
0000 95  : EXTERNAL SYMBOLS:
0000 96  :
0000 97
0000 98      .DSABL  GBL      ; Declare all external symbols
0000 99      .EXTRN  FOR$$IO_BEG      ; common I/O statement processing
0000 100
0000 101  :+ The following references are to make sure the necessary UDF and REC
0000 102  : modules are loaded. These are the routines which are called through
0000 103  : the dispatch tables in FOR$$DISPAT.
0000 104  :-
0000 105      .EXTRN  FOR$$UDF_WF0, FOR$$UDF_WF1, FOR$$UDF_WF9
0000 106      .EXTRN  FOR$$REC_WMF0, FOR$$REC_WMF1, FOR$$REC_WMF9
0000 107
0000 108  :
0000 109  : MACROS:
0000 110
0000 111      NONE
0000 112
0000 113  : PSECT DECLARATIONS:
0000 114  :
0000 115
0000 116      .PSECT  _FOR$CODE PIC,USR,CON,REL,LCL,SHR,EXE,RD,NOWRT,LONG
0000 117
0000 118  :
0000 119  : EQUATED SYMBOLS:
0000 120  :
0000 121
0000 122
0000 123  :
0000 124  : OWN STORAGE:
0000 125
0000 126      NONE
0000 127  :
```

```
0000 129 .SBTTL FOR$ENCODE_MF - ENCODE formatted
0000 130
0000 131 :++
0000 132 : FUNCTIONAL DESCRIPTION:
0000 133 :
0000 134 : Initialize the FORTRAN I/O system to perform
0000 135 : a ENCODE formatted I/O statement.
0000 136
0000 137 CALLING SEQUENCE:
0000 138
0000 139 CALL FOR$ENCODE_MF (char_cnt.rlu.v, format_adr.mbu.ra, usr_buf_adr.wt.ra
0000 140 [, err_adr.j.r [, end_adr.j.r]])
0000 141
0000 142 INPUT PARAMETERS:
0000 143
0000 144 unit.rl.v logical unit number
0000 145 format_adr.mbu.ra adr. of compiled format byte array
0000 146 usr_buf_adr.wt.ra adr. of user's buffer
0000 147 [err_adr.j.r] optional ERR= address
0000 148 [end_adr.j.r] optional END= address
0000 149
0000 150 IMPLICIT INPUTS:
0000 151
0000 152 NONE except those used by FOR$$IO_BEG.
0000 153
0000 154 OUTPUT PARAMETERS:
0000 155
0000 156 NONE
0000 157
0000 158 IMPLICIT OUTPUTS:
0000 159
0000 160 NONE except those left by FOR$$IO_BEG.
0000 161
0000 162 COMPLETION CODES:
0000 163
0000 164 NONE
0000 165
0000 166 SIDE EFFECTS:
0000 167
0000 168 NONE except those of FOR$$IO_BEG.
0000 169
0000 170 :--
0000 171
0000 172 FOR$ENCODE_MF:: .MASK FOR$$IO_BEG
50 0B 9A 0002 173 MOVZBL #ISB$K_ST_TY_WMF, R0 ; Statement type
00000002'GF 17 0005 174 JMP G^FOR$$IO_BEG+2 ; branch past call mask
000B 175
000B 176
000B 177 .END
```

FOR\$ENCODE MF  
Symbol table

- entry point for FORTRAN ENCODE FORMATT M 2  
15-SEP-1984 23:51:30 VAX/VMS Macro V04-00 Page 5  
6-SEP-1984 10:55:00 [FORRTL.SRC]FORENCOMF.MAR;1 (4)

FOR\$\$IO BEG	*****	X	00
FOR\$\$REC_WMFO	*****	X	00
FOR\$\$REC_WMFI	*****	X	00
FOR\$\$REC_WMF9	*****	X	00
FOR\$\$UDF_WFO	*****	X	00
FOR\$\$UDF_WFI	*****	X	00
FOR\$\$UDF_WF9	*****	X	00
FOR\$ENCODE MF	00000000	RG	01
ISB\$K_ST_TV_WMF	= 0000000B		

-----  
! Psect synopsis !  
-----

PSECT name	Allocation	PSECT No.	Attributes												
ABS	00000000 ( 0.)	00 ( 0.)	NOPIC	USR	CON	ABS	LCL	NOSHR	NOEXE	NORD	NOWRT	NOVEC	BYTE		
_FOR\$CODE	0000000B ( 11.)	01 ( 1.)	PIC	USR	CON	REL	LCL	SHR	EXE	RD	NOWRT	NOVEC	LONG		

-----  
! Performance indicators !  
-----

Phase	Page faults	CPU Time	Elapsed Time
Initialization	31	00:00:00.08	00:00:00.80
Command processing	117	00:00:00.58	00:00:03.15
Pass 1	124	00:00:01.27	00:00:04.84
Symbol table sort	0	00:00:00.19	00:00:00.28
Pass 2	48	00:00:00.49	00:00:01.67
Symbol table output	3	00:00:00.02	00:00:00.02
Psect synopsis output	2	00:00:00.00	00:00:00.04
Cross-reference output	0	00:00:00.00	00:00:00.00
Assembler run totals	327	00:00:02.66	00:00:10.83

The working set limit was 900 pages.  
6671 bytes (14 pages) of virtual memory were used to buffer the intermediate code.  
There were 20 pages of symbol table space allocated to hold 187 non-local and 0 local symbols.  
177 source lines were read in Pass 1, producing 8 object records in Pass 2.  
9 pages of virtual memory were used to define 2 macros.

-----  
! Macro library statistics !  
-----

Macro library name	Macros defined
_\$255\$DUA28:[FORRTL.OBJ]FORRTL.MLB;1	2
_\$255\$DUA28:[SYSLIB]STARLET.MLB;2	0
TOTALS (all libraries)	2

183 GETS were required to define 2 macros.

There were no errors, warnings or information messages.

MACRO/ENABLE=SUPPRESSION/DISABLE=(GLOBAL,TRACEBACK)/LIS=LIS\$:FORENCOMF/OBJ=OBJ\$:FORENCOMF MSRC\$:FORENCOMF/UPDATE=(ENH\$:FORENCOMF)+L I



0180 AH-BT13A-SE  
VAX/VMS V4.0

DIGITAL EQUIPMENT CORPORATION  
CONFIDENTIAL AND PROPRIETARY

